




Product Description: Spryte™ 10W Fixed Integrated IP44 Dimmable LED Downlight


Spryte™ LED downlight range is the ideal energy efficient non-fire rated solution for new build or retrofit halogen reflector lamp installations. Fitted with the edge-to-edge, multifaceted 60° wide beam EnFiniti™ lens, these downlights allow for high light output and low glare while still providing a sparkling halogen like optical appearance in a compact sized fitting. Now also available in 8W ball-joint adjustable version alongside the fixed for maximum application flexibility.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-DDL1019AK/27	10	2700	810	81	60	White	Dimmable
EN-DDL1019AK/30	10	3000	1000	100	60	White	Dimmable
EN-DDL1019AK/40	10	4000	1050	105	60	White	Dimmable
EN-DDL1019AK/64	10	6400	1100	110	60	White	Dimmable

Line Drawing



Polar Curve



Colour

Feature & Benefits

- Energy efficient LED downlight for new build or halogen and reflector lamp retrofit applications
- ThermoTec™ technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- EnFiniti™ edge-to-edge multifaceted polycarbonate lens creates low glare and halogen like appearance
- Compact integrated driver for easy installation and low ceiling voids
- 8W supplied with fixed white bezel. 10W supplied with interchangeable round & square white bezels
- 60 degree version IP44 rated. 90 degree version IP40 rated
- Ideal for residential applications such as corridors, bedrooms, dining rooms, lounge areas and zone 2 of bathrooms
- Pre-wired with 1.2m flex and 2-pin plug
- 1.5kV surge protection
- 3 year warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	/50HZ
Power Factor	0.5	IP Rating	IP44
Lifetime L70 (hrs)	25000hrs	Overall Diameter (mm)	105
Height (mm)	57	Product Type	Downlights
Cutout Diameter (mm)	82-90		

Compliance & Approvals:

Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.