




Product Description: ReflectCS[™] 18W IP54 Colour Switchable Downlight

The ReflectCS[™] range is a colour switchable downlight with a high powered SMD. Featuring a sparkling multifaceted aluminium reflector designed for exceptional light control and providing a 60 degree beam angle for focused downlighting. The downlight can be switchable between 3000K (1770 lumens), 4000K (1840 lumens) and 5700K (1760 lumens).


With this versatile downlight, by making your colour selection prior to install it makes it ideal for various applications. Please note: lumen value in SKU table is stated at 4000K.

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
EN-DDL186CCT	18	3000K	1780	60	White	Triac Dimmable
EN-DDL186CCT	18	4000K	1820	60	White	Triac Dimmable
EN-DDL186CCT	18	5700K	1770	60	White	Triac Dimmable
EN-DDL186CCTDA	18	3000K	1780	60	White	DALI Dimmable
EN-DDL186CCTDA	18	4000K	1820	60	White	DALI Dimmable
EN-DDL186CCTDA	18	5700K	1770	60	White	DALI Dimmable
EN-DDL186CCTV	18	3000K	1780	60	White	1-10V Dimmable
EN-DDL186CCTV	18	4000K	1820	60	White	1-10V Dimmable
EN-DDL186CCTV	18	5700K	1770	60	White	1-10V Dimmable


Line Drawing



Polar Curve



Colour



White

Feature & Benefits

- Colour switchable between 3000K, 4000K & 5700K
- High powered SMD with a multifaceted aluminium reflector
- Delivering up to 102m/W (at 4000K)
- Lumen Value at 3000K - 1780lm
- Lumen Value at 4000K - 1820lm
- Lumen Value at 5700K - 1770lm
- 60° beam angle
- IP54 rated
- Supplied with remote triac dimmable constant current driver
- 5 Year Warranty
- 3 year onsite warranty (registration required) *Terms and conditions apply

Product Specs:

Input Voltage	200~240V AC	Power Factor	0.9
IP Rating	IP54	Lifetime L70 (hrs)	50000hrs
Overall Diameter (mm)	190	Weight (Kg)	0.445
Height (mm)	90	Product Type	Downlights
Cutout Diameter (mm)	160-170	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	40°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.