




**Product Description:** ReflectCS<sup>™</sup> 35W IP54 Colour Switchable Downlight

The ReflectCS<sup>™</sup> range is a colour switchable downlight with a high powered SMD. Featuring a sparkling multifaceted aluminium reflector designed for exceptional light control and providing a 60 degree beam angle for focused downlighting. The downlight can be switchable between 3000K (3990 lumens), 4000K (3600 lumens) and 5700K (3440 lumens).

With this versatile downlight, by making your colour selection prior to install it makes it ideal for various applications. Please note: lumen value in SKU table is stated at 4000K.


SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
EN-DDL358CCT	35	3000K	3390	60	White	Triac Dimmable
EN-DDL358CCT	35	4000K	3600	60	White	Triac Dimmable
EN-DDL358CCT	35	5700K	3400	60	White	Triac Dimmable
EN-DDL358CCTDA	35	3000K	3390	60	White	DALI Dimmable
EN-DDL358CCTDA	35	4000K	3600	60	White	DALI Dimmable
EN-DDL358CCTDA	35	5700K	3400	60	White	DALI Dimmable
EN-DDL358CCTV	35	3000K	3390	60	White	1-10V Dimmable
EN-DDL358CCTV	35	4000K	3600	60	White	1-10V Dimmable
EN-DDL358CCTV	35	5700K	3400	60	White	1-10V Dimmable

## Line Drawing



## Polar Curve

## Colour



White

## Feature & Benefits

- Colour switchable between 3000K, 4000K & 5700K
- High powered SMD with a multifaceted aluminium reflector
- Delivering up to 103m/W (at 4000K)
- Lumen Value at 3000K - 3390lm
- Lumen Value at 4000K - 3600lm
- Lumen Value at 5700K - 3440lm
- 60° beam angle
- IP54 rated
- Supplied with remote triac dimmable constant current driver
- 5 Year Warranty
- 3 year onsite warranty (registration required) \*Terms and conditions apply

## Product Specs:

Input Voltage	200~240V AC	Power Factor	0.9
IP Rating	IP54	Lifetime L70 (hrs)	50000hrs
Overall Diameter (mm)	235	Weight (Kg)	0.664
Height (mm)	100	Product Type	Downlights
Cutout Diameter (mm)	200-210	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	40°C		

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.