





Product Description:

OD

# Reflector-Fit<sup>™</sup> 18W Triac Dimmable Downlight

The Reflector-Fit<sup>™</sup> range comes with a high powered COB which can provide up to 122lm/W. Featuring a sparkling multifaceted aluminium reflector designed for exceptional light control and providing a 60 degree beam angle for focused downlighting. Available in four different wattage's.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-DDL818/40	18	4000	2200	123	60	White	Triac Dimmable
EN-DDL818DA/40	18	4000	2200	123	60	White	DALI Dimmable
EN-DDL818V/40	18	4000	2200	123	60	White	1-10V Dimmable
Line Drawing		Polar Cu	urve		Colour		
					White		

## Feature & Benefits

#### Energy efficent COB LED downlights

- 60° beam angle
- Triac dimmable as standard
- Plug and play remote driver for easy installation
- IP44 rated
- 1.5kV surge protection
- SEAI: EN-DDL818/40 -LIG84986
- 3 Year Warranty

### **Product Specs:**

Input Voltage	200~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	40000hrs
Weight (Kg)	1.356
Product Type	Downlights
Operating Temp. (Min) °C	-20°C

Input Frequency	50/HZ
IP Rating	IP44
Overall Diameter (mm)	225
Height (mm)	87
Cutout Diameter (mm)	200-210
Operating Temp. (Max) °C	45°C

## Compliance & Approvals:



### Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.