




**Product Description:** Reflector-Fit<sup>™</sup> 40W Triac Dimmable Downlight


The Reflector-Fit<sup>™</sup> range comes with a high powered COB which can provide up to 122lm/W. Featuring a sparkling multifaceted aluminium reflector designed for exceptional light control and providing a 60 degree beam angle for focused downlighting. Available in four different wattage's.

| SKU Code       | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type       |
|----------------|---------|--------|--------|-------------|------------|---------------|----------------|
| EN-DDL840/40   | 40      | 4000   | 4450   | 112         | 60         | White         | Triac Dimmable |
| EN-DDL840DA/40 | 40      | 4000   | 4450   | 112         | 60         | White         | DALI Dimmable  |
| EN-DDL840V/40  | 40      | 4000   | 4450   | 112         | 60         | White         | 1-10V Dimmable |


**Line Drawing**



**Polar Curve**



**Colour**



White

## Feature & Benefits

- Energy efficient COB LED downlights
- 60° beam angle
- Triac dimmable as standard
- Plug and play remote driver for easy installation
- IP44 rated
- 1.5kV surge protection
- SEAI: EN-DDL840/40 - LIG84988
- 3 Year Warranty

## Product Specs:

|                          |             |                          |         |
|--------------------------|-------------|--------------------------|---------|
| Input Voltage            | 200~240V AC | Input Frequency          | 50/HZ   |
| Power Factor             | 0.9         | IP Rating                | IP44    |
| Lifetime L70 (hrs)       | 40000hrs    | Overall Diameter (mm)    | 225     |
| Weight (Kg)              | 1.469       | Height (mm)              | 87      |
| Product Type             | Downlights  | Cutout Diameter (mm)     | 200-210 |
| Operating Temp. (Min) °C | -20°C       | Operating Temp. (Max) °C | 45°C    |

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.