




Product Description: E6[™] PRO Adjustable 6W Dimmable Fire Rated Downlight


The E6[™] PRO is a revolution in LED downlight performance and installation. Utilising the unique RapidWire connection system, the whole product can be fully wired and installed in a matter of seconds. The use of latching terminals provides the security of screw terminations for both solid and stranded core cables and can be wired even faster than standard push fits. The removable connector allows full circuit insulation resistance testing without risking any damage to the downlight, which can be simply plugged in afterwards.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-DE62PROMW/30	6	3000	680	114	60	Matt White	Triac Dimmable
EN-DE62PROMW/40	6	4000	700	117	60	Matt White	Triac Dimmable
EN-DE62PROPC/30	6	3000	680	114	60	Polished Chrome	Triac Dimmable
EN-DE62PROPC/40	6	4000	700	117	60	Polished Chrome	Triac Dimmable
EN-DE62PROSN/30	6	3000	680	114	60	Satin Nickel	Triac Dimmable
EN-DE62PROSN/40	6	4000	700	117	60	Satin Nickel	Triac Dimmable
EN-DE62PROW/30	6	3000	680	114	60	White	Triac Dimmable
EN-DE62PROW/40	6	4000	700	117	60	White	Triac Dimmable


Line Drawing




Polar Curve




Colour




Matt White



Polished
Chrome



Satin Nickel



White

Feature & Benefits

- Quick, easy and fully tool-free installation
- Connector for first fix & insulation resistance testing
- High performance up to 117lm/W
- EnFiniti™ edge-to-edge multifaceted polycarbonate lens for low glare and halogen like appearance
- Wide 60° beam angle delivers increased light distribution
- Fibre based insulation coverable - up to 300mm
- Slim IP65 bezels provide a high end sleek finish
- Compatible with Aurora FastRfix™ connector
- Tested in 30, 60 and 90 min fire rated ceilings
- Fire tested with solid timber, joist and metal web joists
- SEAI: EN-DE62PRO/30 - LIG84982
- SEAI: EN-DE62PRO/40 - LIG84983
- 5 year warranty

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.8
Lifetime L70 (hrs)	50000hrs
Overall Diameter (mm)	95
Height (mm)	105
Cutout Diameter (mm)	80-80

Input Frequency	50/60HZ
IP Rating	IP20
Lamp Base	None
Weight (Kg)	0.407
Product Type	Downlights, Fire-Rated Downlight

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.