




Product Description: Uni-Fit[™] 15W Integrated IP44 Non-Dimmable Downlight

Performance and Value - that's what the Uni-Fit[™] range of commercial downlights stands for. Featuring ThermoTec[™] technology, integrated driver and high quality LED chips to deliver an outstanding lumen performance. Uni-Fit[™] range is the ideal cost effective solution for new or existing installations where traditional compact fluorescent downlights need upgrading to more efficient LED technology.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type |
|------------|---------|--------|--------|-------------|------------|---------------|--------------|
| EN-DL15/30 | 15 | 3000 | 1600 | 107 | 100 | White | Non Dimmable |
| EN-DL15/40 | 15 | 4000 | 1700 | 114 | 100 | White | Non Dimmable |

Line Drawing



Polar Curve

Colour



White

Feature & Benefits

- Multiple sizes and wattages available to suit all new and retrofit installation lighting requirements
- ThermoTec™ technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- Compact integrated driver for easy installation and shallow ceiling voids
- Life not affected by frequent switching e.g. when used with occupancy controls
- IP44 rated
- TP(b) rated
- Pre-wired with 500mm 2 core cable
- 1.5kV surge protection
- 3 year warranty

Product Specs:

| | | | |
|--------------------------|-------------|--------------------------|---------|
| Input Voltage | 220~240V AC | Input Frequency | 50/60HZ |
| Power Factor | 0.9 | IP Rating | IP44 |
| Lifetime L70 (hrs) | 25000hrs | IK Rating | IK03 |
| Lamp Base | None | Overall Diameter (mm) | 150 |
| Weight (Kg) | 0.234 | Height (mm) | 60 |
| Product Type | Downlights | Cutout Diameter (mm) | 120-120 |
| Operating Temp. (Min) °C | -20°C | Operating Temp. (Max) °C | 40°C |

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.