




Product Description: CurveE[™] 10W Baffled Dimmable IP44 Downlight


Introducing the stylish CurveE[™] LED downlight range, this low glare downlight has a sleek baffled design with the light source recessed back to reduce glare. Available in matt white these triac dimmable downlights are an ideal non-fire rated solution for hospitality and residential applications in areas where fire rating is not required.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type |
|-----------------|---------|--------|--------|-------------|------------|---------------|----------------|
| EN-DLB101D/30 | 10 | 3000 | 920 | 92 | 60 | White | Triac Dimmable |
| EN-DLB101D/40 | 10 | 4000 | 970 | 97 | 60 | White | Triac Dimmable |
| EN-DLB101DDA/30 | 10 | 3000 | 920 | 92 | 60 | White | DALI Dimmable |
| EN-DLB101DDA/40 | 10 | 4000 | 970 | 97 | 60 | White | DALI Dimmable |
| EN-DLB101DV/30 | 10 | 3000 | 920 | 92 | 60 | White | 1-10V Dimmable |
| EN-DLB101DV/40 | 10 | 4000 | 970 | 97 | 60 | White | 1-10V Dimmable |


Line Drawing



Polar Curve



Colour



Matt White

Feature & Benefits

- Baffled design for low glare - LED recessed by 10mm
- Plug and play remote driver for easy installation
- IP44 rated - ideal for hospitality and residential applications such as corridors, living areas, bedrooms, dining rooms and zone 2 of bathrooms
- UGR19 (Unified Glare Rating)
- 1.5kV surge protection
- 5 year warranty
- 3 year onsite warranty (registration required) *Terms and conditions apply

Product Specs:

| | | | |
|--------------------------|-------------|--------------------------|------------|
| Input Voltage | 220~240V AC | Power Factor | 0.90 |
| IP Rating | IP44 | Lifetime L70 (hrs) | 50000hrs |
| IK Rating | IK02 | Lamp Base | None |
| Overall Diameter (mm) | 80 | Weight (Kg) | 0.245 |
| Height (mm) | 60 | Product Type | Downlights |
| Cutout Diameter (mm) | 70-72 | Operating Temp. (Min) °C | -20°C |
| Operating Temp. (Max) °C | 45°C | | |

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.