




**Product Description:** 3W 3 Hour Non-Maintained Emergency with Self Test Function


3W self testing emergency non-maintained downlight comes with interchangeable lenses, offering flexibility in installation. Includes LED driver and lithium-ion battery. Compact downlight fits into a 45mm cut-out. Overall length, ribbon and hard case dimensions - 570mm.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-EMLD5ST	3	6000	270	90	120	White	Emergency


**Line Drawing**



**Polar Curve**




Corridor Lens



Open Space Lens

**Colour**



White

## Feature & Benefits

- Self test non-maintained LED emergency downlight with interchangeable lenses
- Interchangeable lenses offer a corridor (75° beam angle) or open space (120° beam angle) light distribution
- 3 hour emergency duration
- Compact downlight fits into a 45-48mm cut-out
- 3 Year Warranty

## Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.5	IP Rating	IP20
Overall Diameter (mm)	60	Weight (Kg)	0.251
Height (mm)	26	Product Type	Power/Control, Emergency
Cutout Diameter (mm)	45-48		

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.