



Product Description:

100-240V Non-rotatable 1500mm T8 Frosted LED Tube

LED tubes is a cost effective solution for either retrofitting existing T8 fittings or in new installations. Utilising the latest LED technology, they use 50% less energy when compared to traditional fluorescent T8 tubes.

SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	CRI
EN-ET81524FR/40	4000	2000	84	24	160	80
		Dalar Currie		Cold		
Line Drawing		Polar Curve		Colo		
Feature & Benefits						
 360° impact resistant frosted polycarbonate housing improves aesthetics and durability 	more lig • Wide 16	up to 881m/W delivers ht using less energy 0° beam angle delivers ed light distribution	 Suitable for use at -20° to +40°C making the range ideal for multiple applications and environments 2 year warranty 			
• LED starter included, preventing risk of electric shock when tubes are inserted or removed from luminaire	11016436		 Life not affected by frequent switching e.g. when used with occupancy controls 			

Product Specs:

Input Voltage	100~240V AC	Input Frequency	50/60HZ
Power Factor	0.95	Operating Temp. (Max) °C	40°C
Overall Diameter (mm)	26	Lamp Base	G13
Lamp Type	Т8	Weight (Kg)	0.379
Lifetime Hours	25000hrs	Operating Temp. (Min) °C	-20

Compliance & Approvals:



Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.