





Product Description:

Helius+™ 200W Adjustable IP65 LED Floodlight

Same design but improved efficacy, the Helius<sup>TM</sup>+ floodlights have been upgraded to 100lm/W. Featuring SMD LED chips these floodlights are perfect for both residential and commercial IP65 applications. Their slim profile and clean black finish make them as unobtrusive as possible. Available in 10W, 30W, 50W, 100W, 200W and 300W versions with black housing with the options to wall mount them with the stem accessory or put them in the ground with the spike accessory sold separately.

| SKU Code     | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|--------------|---------|--------|--------|-------------|------------|---------------|
| EN-FL200B/40 | 200     | 4000   | 20000  | 100         | 120        | Black         |
| EN-FL200B/65 | 200     | 6500   | 20000  | 100         | 120        | Black         |







Black

## Feature & Benefits

- IP65 rated LED floodlight rated with slim design
- Durable high quality paint minimises impact of corrosion
- Tempered glass provides excellent protection
- Die-cast aluminium housing
- Pre-wired with 800mm of cable
  3 year warranty
- 1.5kV surge protection

## **Product Specs:**

| Input Voltage            | 100~240V AC |  |  |
|--------------------------|-------------|--|--|
| Power Factor             | 0.9         |  |  |
| Lifetime L70 (hrs)       | 25000hrs    |  |  |
| Lamp Base                | None        |  |  |
| Length (mm)              | 380         |  |  |
| Height (mm)              | 380         |  |  |
| Operating Temp. (Min) °C | -30°C       |  |  |

| Input Frequency          | 50/60HZ     |
|--------------------------|-------------|
| IP Rating                | IP65        |
| IK Rating                | IK08        |
| Width (mm)               | 380         |
| Weight (Kg)              | 8.088       |
| Product Type             | Floodlights |
| Operating Temp. (Max) °C | 35°C        |

## Compliance & Approvals:



















This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.