AURORA® LIGHTING

Helius™




Product Description: Helius™ 30W Adjustable IP65 Floodlight

The Helius™ range of floodlights are perfect for both residential and commercial IP65 applications. Their slim profile and clean black finish make them as unobtrusive as possible. Available in 10W, 30W, 50W, 100W, 200W and 300W versions with black housing.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-FL30A/40	30	4000	2250	75	120	Black	Non Dimmable

Line Drawing



Polar Curve

Colour

Black

Feature & Benefits

- IP65 rated LED floodlight rated with slim design
- Durable high quality paint minimises impact of corrosion
- Tempered glass provides excellent protection
- Die-cast aluminium housing
- Pre-wired with 800mm of cable
- 1.5kV surge protection
- Warning Note: Not suitable for post top mounting
- 3 year warranty

Product Specs:

Input Voltage	110~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	25000hrs
Lamp Base	None
Weight (Kg)	1.682
Product Type	Floodlights

Input Frequency	50/60HZ
IP Rating	IP65
IK Rating	IK08
Width (mm)	195
Height (mm)	230

Compliance & Approvals:

Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.