




**Product Description:** Volta<sup>™</sup> 80W Adjustable IP65 Floodlight


The IP65 driverless range of Volta<sup>™</sup> offers a comprehensive range of beam angles to suit different commercial applications. With their ultra slim profile and high performance, now you can light large external areas with the choice of Narrow, wide and asymmetric beams.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-FLC80AB/40	80	4000	9600	120	65	Black	Non Dimmable
EN-FLC80NB/40	80	4000	9600	120	60	Black	Non Dimmable
EN-FLC80WB/40	80	4000	9600	120	90	Black	Non Dimmable


## Line Drawing




## Polar Curve



Asymmetric



Narrow



Wide

## Colour



Black

## Feature & Benefits

### Product Specs:

Input Voltage	100~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	50000hrs	IK Rating	IK08
Lamp Base	None	Width (mm)	286
Weight (Kg)	4.179	Height (mm)	365
Product Type	Floodlights	Operating Temp. (Min) °C	-40°C
Operating Temp. (Max) °C	50°C		

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.