




**Product Description:** Proxima<sup>™</sup> 50W Adjustable IP65 LED Floodlight


Offering an excellent 120lm/W, the Proxima<sup>™</sup> floodlight range provides the perfect solution for residential and commercial applications. With the product being IP65 and salt spray tested, it offers a solution for coastal applications. Available in 50W, 100W and 200W.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-FLP50/40	50	4000	6000	120	100	Black	Non Dimmable

**Line Drawing**



**Polar Curve**



**Colour**



Black

## Feature & Benefits

- Aluminium housing for excellent heat dissipation
- Salt spray tested
- IP65 rated
- IK08 rated
- Pre-wired with 800mm of cable
- L80 50,000hrs
- 5 Year Warranty
- 3 year onsite warranty (registration required) \*Terms and conditions apply

## Product Specs:

Input Voltage	100~277V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	50000hrs	IK Rating	IK08
Width (mm)	195	Weight (Kg)	1.098
Height (mm)	153	Product Type	Floodlights
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.