





Product Description:

Vela™ 50W Adjustable IP65 Driverless Floodlight

Lumens/Watt Beam Angle Finish Colour

The IP65 driverless range of Vela[™] floodlights comes complete with an ultra slim profile and high performance. Delivering 120lm/W and with the product being salt spray tested, it offers a solution for coastal applications.

EN-FLV50/40	50	4000	6000	120	110	Black	Non Dimmable
Line Drawing		Polar Cu	urve		Colour		
BL BW		137	127 127 127 127		Black		

Feature & Benefits

- Aluminium housing for excellent IP65 rated heat dissipation
 - IK06 rated
- Pre-wired with 800mm of cableL70 30,000hrs

Tempered frosted glass

 Salt spray tested and approved 3 Year Warranty

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	30000hrs
Width (mm)	196
Product Type	Floodlights
Operating Temp. (Max) °C	45°C

Input Frequency	50/60HZ
IP Rating	IP65
IK Rating	IK06
Height (mm)	143
Operating Temp. (Min) °C	-35°C

Compliance & Approvals:











This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.