



Product Description: E1230™ 1200mm x 300mm 36W LED Light Panel

The E1230™ has been upgraded to produce 95lm/W for outstanding energy savings. The light guide board and diffuser have been engineered to ensure maximum light output and complete uniformity. Suitable for a wide range of applications including office, education and commercial spaces.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-FP1230CAK/30	36	3000	3200	89	110	RAL9016	Non Dimmable
EN-FP1230CAK/40	36	4000	3400	95	110	RAL9016	Non Dimmable
EN-FP1230CAK/50	36	5000	3400	95	110	RAL9016	Non Dimmable
EN-FP1230CDAK/30	36	3000	3200	89	110	RAL9016	DALI Dimmable
EN-FP1230CDAK/40	36	4000	3400	95	110	RAL9016	DALI Dimmable
EN-FP1230CDAK/50	36	5000	3400	95	110	RAL9016	DALI Dimmable
EN-FP1230CVAK/30	36	3000	3200	89	110	RAL9016	Dimmable
EN-FP1230CVAK/40	36	4000	3400	95	110	RAL9016	Dimmable
EN-FP1230CVAK/50	36	5000	3400	95	110	RAL9016	Dimmable

Line Drawing

Polar Curve

Colour

Feature & Benefits

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP20
Lifetime L70 (hrs)	30000hrs	Width (mm)	295
Length (mm)	1195	Height (mm)	10
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

Compliance & Approvals:



Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.