

Product Description:

625 x 625mm 40W Non-Dimmable LED Flat Panel

The new ultra-slim E6262[™] edge-lit LED panel range is suitable for a wide range of applications including office, education and commercial spaces. The advanced aluminium heat sink dissipates unwanted heat allowing for a flat form factor. The range is engineered to deliver a Unified Glare Rating of 19 (UGR19) for even light distribution.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
EN-FP6262DE/40	40	4000	3600	90	115	RAL9016
Line Drawing		Polar Curve		Colo	ur	
Feature & Benefits						
 Edge-lit design and optical pattern light guide engineered for even light distribution Suitable for installation in 15 & 24mm T-bar ceilings SDCM <4 providing consistent light colour quality 	suitable Flicker f Factor > Life not switchin	(Unified Glare Rating) - for use in offices ree driver - Power 0.9 affected by frequent g e.g. when used with icy controls	emergency Surface model 	mable and separate pack available ount box and suspension kit	 1.5kV surge 3 year warrar 	·
Product Specs:						

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	Lifetime L70 (hrs)	40000hrs
Width (mm)	622	Length (mm)	622
Weight (Kg)	3.695	Height (mm)	9.5

Compliance & Approvals:

Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.