


Product Description:

E1260™ PRO 1200 x 600mm 50W LED Flat Panel

The E6060TM, E1230TM and E1260TM PRO range delivers an industry leading 110lm/W, producing over 60% energy savings compared to traditional fluorescent.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-FPR01260/40	50	4000	5500	110	110	White	Non Dimmable
EN-FPR01260/50	50	5000	5500	110	110	White	Non Dimmable
EN-FPR01260DA/40	50	4000	5500	110	110	White	DALI Dimmable
EN-FPR01260DA/50	50	5000	5500	110	110	White	DALI Dimmable
EN-FPR01260V/40	50	4000	5500	110	110	White	1-10V Dimmable
EN-FPR01260V/50	50	5000	5500	110	110	White	1-10V Dimmable





Feature & Benefits

- Edge-lit design and optical pattern light guide engineered for even light distribution
- Suitable for installation in 15 & 24mm T-bar ceilings
- RAL2016

- SDCM <4 providing consistent light colour quality
- UGR 19 (Unified Glare Rating) suitable for use in offices
- Flicker free driver Power Factor >0.9
- 1-10V dimmable, DALI and emergency versions available
- Surface mount box, ceiling recess box and adjustable suspension kit available
- 1.5kV surge protection
- 5 year warranty

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	50000hrs
Lamp Base	None
Length (mm)	1195
Height (mm)	10
Operating Temp. (Min) °C	-10°C

Input Frequency	50/60HZ		
IP Rating	IP20		
IK Rating	IK06		
Width (mm)	595		
Weight (Kg)	5.802		
Product Type	Panels		
Operating Temp. (Max) °C	40°C		

Colour

Compliance & Approvals:













Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.