





## **Product Description:**

## EdgeLite<sup>™</sup> 1200 x 600mm 50W Flat Panel

The EdgeLite<sup>™</sup> range delivers an industry leading 110lm/W, producing over 60% energy savings compared to traditional fluorescent and is TP(b) rated. A superior level of construction results in an IP44 rating as standard for damp environments.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-FPR01260B/40	50	4000	5500	110	110	White	Non Dimmable
EN-FPR01260B/50	50	5000	5500	110	110	White	Non Dimmable
EN-FPR01260BDA/40	50	4000	5500	110	110	White	DALI Dimmable
EN-FPR01260BDA/50	50	5000	5500	110	110	White	DALI Dimmable
EN-FPR01260BV/40	50	4000	5500	110	110	White	1-10V Dimmable
EN-FPR01260BV/50	50	5000	5500	110	110	White	1-10V Dimmable

Line Drawing	Polar Curve	Color	ur
		White	3
<ul> <li>Feature &amp; Benefits</li> <li>Edge-lit design and optical pattern light guide engineered for even light distribution</li> </ul>	<ul> <li>High quality PMMA light guide designed to prevent yellowing</li> </ul>	• UGR 19 (Unified Glare Rating) - suitable for use in offices	<ul> <li>Surface mount box, ceiling recess box and adjustable suspension kit available</li> </ul>
<ul> <li>Suitable for installation in 15 &amp; 24mm T-bar ceilings</li> <li>RAL2016</li> </ul>	<ul> <li>SDCM &lt;4 providing consistent light colour quality</li> <li>TP(b) rated</li> </ul>	<ul> <li>Flicker free driver - Power Factor &gt;0.9</li> <li>1-10V dimmable, DALI and emergency versions available</li> </ul>	<ul><li> 1.5kV surge protection</li><li> 5 year warranty</li></ul>
Product Specs:			
Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP20
Lifetime L70 (hrs)	50000hrs	IK Rating	IK06

	0.5
Lifetime L70 (hrs)	50000hrs
Lamp Base	None
Length (mm)	1195
Height (mm)	10
Operating Temp. (Min) °C	-10°C

Input Frequency	50/60HZ
IP Rating	IP20
IK Rating	IK06
Width (mm)	595
Weight (Kg)	5.489
Product Type	Panels
Operating Temp. (Max) °C	40°C

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.