




SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	Finish Colour	Product Type
EN-HB200AK/40	4000	22000	110	200	120	Black	Standard
EN-HB200AK/60	6000	21000	105	200	120	Black	Standard

Line Drawing      Polar Curve      Color



## Product Features:

- IP65 rated and die-cast housing for maximum protection in all environments - IK08 impact rating
- High thermal efficient aluminium heatsink - low operating temperature
- 1-10V dimming function built in as standard - allows for use with daylight or occupancy sensors
- Significant energy savings and reduced maintenance over HID highbays
- Ideal for use in warehousing, manufacturing, conference centres, industrial lighting, canopies etc
- High power factor of 0.95
- 120° beam angle as standard, optional 60° or 90° and acrylic reflectors available
- Suspension and wall mounting options
- Pre-wired with 1.5m flex and 2-pin plug
- Max ambient temperature 50°C
- 1.5kV surge protection
- 5 year warranty

## Product Specs:

Input Voltage	100~240V AC	Input Frequency	50/60HZ
Power Factor	0.95	Dimmable	Yes
Number of LEDs	252	IP Rating	IP65
Technology	LED	Luminaire Distribution	Direct
Lifetime L70 (hrs)	50000	IK Rating	IK08
Operating Temp	50°C	Optic Material	Glass
Overall Diameter (mm)	400	Positional Adjustment	Fixed
SDCM	6	LED Chip	3030
Positional Adjustment	Fixed		

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.