




**Product Description:** InterLED<sup>™</sup> 1500mm 40W Linear


Supplied with 2m suspension cable and surface mount brackets, the InterLED<sup>™</sup> is an LED linear batten suitable for a range of applications. Delivering 100lm/W the opal polycarbonate diffuser ensures uniform light distribution. Available in a choice of white or black finish, with the option to add an emergency pack.

| SKU Code          | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type     |
|-------------------|---------|--------|--------|-------------|------------|---------------|--------------|
| EN-LN1540BLK/40   | 40      | 4000   | 4000   | 100         | 110        | Black         | Non Dimmable |
| EN-LN1540EMBLK/40 | 40      | 4000   | 4000   | 100         | 110        | Black         | Emergency    |
| EN-LN1540EMW/40   | 40      | 4000   | 4000   | 100         | 110        | White         | Emergency    |
| EN-LN1540W/40     | 40      | 4000   | 4000   | 100         | 110        | White         | Non Dimmable |

## Line Drawing




## Polar Curve



## Colour



Black



White

## Feature & Benefits

- Opal polycarbonate diffuser with uniform distribution
- Delivering 100lm/W
- Supplied with 2m suspension cable & surface mount brackets
- Suitable to be surface mounted or suspended
- 5 Year Warranty

## Product Specs:

|                          |             |                          |          |
|--------------------------|-------------|--------------------------|----------|
| Input Voltage            | 220~240V AC | Power Factor             | 0.9      |
| IP Rating                | IP20        | Lifetime L70 (hrs)       | 50000hrs |
| IK Rating                | IK08        | Width (mm)               | 50       |
| Length (mm)              | 1500        | Weight (Kg)              | 1.914    |
| Height (mm)              | 81.5        | Product Type             | Linears  |
| Operating Temp. (Min) °C | -20°C       | Operating Temp. (Max) °C | 40°C     |

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.