



Product Description:

ET6060 200-240V 600x600mm LED Louvred Troffer


The new ET6060 and ET1230 has a classic louvre design with energy saving LED technology inside. This back-lit louvred troffer has a deep curve aluminium mirror reflector and prismatic diffuser keeping the UGR below 19, ideal for office or education applications with efficacy up to 100lm/W for great energy savings. This luminaire is designed to last with its phosphate treated surfaces, making it more resistant to corrosion and wear.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-LP6060/30	33	3000	3100	94	77	White	Non Dimmable
EN-LP6060/40	33	4000	3300	100	77	White	Non Dimmable

Line Drawing

Polar Curve

Colour



Feature & Benefits

- Back-lit design with prismatic diffuser provides uniformed low glare light output
- 77° beam angle
- UGR <19 (Unified Glare Rating) - suitable for use in offices
- Power Factor > 0.9
- 1-10V and DALI dimmable driver as well as separate emergency pack available
- 1.5kV surge protection

3 year warranty

Product Specs:

Input Voltage	200~240V AC		
Power Factor	0.9		
Lifetime L70 (hrs)	40000hrs		
Length (mm)	595		
Height (mm)	56		
Operating Temp. (Min) °C	-20°C		

Input Frequency	50/60HZ		
IP Rating	IP20		
Width (mm)	595		
Weight (Kg)	3.500		
Product Type	Troffer		
Operating Temp. (Max) °C	45°C		

Compliance & Approvals:















This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.