





Product Description:

EdgeLite[™] 26W 600 x 600mm Flat Panel

The EdgeLite[™] range delivers up to 130lm/W, producing over 60% energy savings compared to traditional fluorescent and TP(a) rated. A superior level of construction results in an IP54 rating as standard for damp environments.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type |
|-----------------|---------|--------|--------|-------------|------------|---------------|----------------|
| EN-LPP6060/40 | 26 | 4000 | 3380 | 130 | 110 | White | Non Dimmable |
| EN-LPP6060/50 | 26 | 5000 | 3380 | 130 | 110 | White | Non Dimmable |
| EN-LPP6060DA/40 | 26 | 4000 | 3380 | 130 | 110 | White | DALI Dimmable |
| EN-LPP6060DA/50 | 26 | 5000 | 3380 | 130 | 110 | White | DALI Dimmable |
| EN-LPP6060V/40 | 26 | 4000 | 3380 | 130 | 110 | White | 1-10V Dimmable |
| EN-LPP6060V/50 | 26 | 5000 | 3380 | 130 | 110 | White | 1-10V Dimmable |

| Line Drawing | Polar Curve | Colour | |
|--------------|-------------|--------|--|
| | | White | |

Feature & Benefits

- Edge-lit design and optical pattern light guide engineered for even light distribution
- Suitable for installation in 15 & 24mm T-bar ceilings
- RAL2016
- SDCM <5 providing consistent light colour quality
- TP(a) rated
- IP54 rated from the front
- UGR 19 (Unified Glare Rating) suitable for use in offices
- Flicker free driver Power Factor >0.9
- 1-10V dimmable, DALI and emergency versions available
- Surface mount box, ceiling recess box and adjustable suspension kit available
- 1.5kV surge protection
- L80 50,000hrs
- 5 year warranty

Product Specs:

| Input Voltage | 220~240V AC |
|--------------------------|-------------|
| Power Factor | 0.9 |
| Lifetime L70 (hrs) | 50000hrs |
| IK Rating | IK07 |
| Width (mm) | 595 |
| Weight (Kg) | 2.370 |
| Product Type | Panels |
| Operating Temp. (Max) °C | 40°C |

| Input Frequency | 50/60HZ |
|--------------------------|----------|
| | |
| IP Rating | IP54 |
| Lifetime L80 (Hours) | 50000hrs |
| Lamp Base | None |
| Length (mm) | 595 |
| Height (mm) | 10 |
| Operating Temp. (Min) °C | -10°C |

Compliance & Approvals:



This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.