



**Product Description:** LEDLine<sup>™</sup> Single Colour Flexible Strip


LEDline<sup>™</sup> single colour LED strip is ideal for both commercial and residential indoor applications such displays and pelmets. Low power consumption of 4.8W per metre. Strip can be cut to length and 2m leads soldered to special order.

| SKU Code     | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|--------------|---------|--------|--------|-------------|------------|---------------|
| EN-ST100/30  | 4.8     | 3000   | 480    | 100         | 120        | White         |
| EN-ST100/40  | 4.8     | 4000   | 500    | 105         | 120        | White         |
| EN-ST100/60  | 4.8     | 6500   | 520    | 109         | 120        | White         |
| EN-ST100/BLU | 4.8     |        |        |             | 120        | White         |

## Line Drawing

## Polar Curve

## Colour



## Feature &amp; Benefits

- Single colour flexible LED strip with 3M™ self adhesive backing
- Beam angle of 120° and 17mm between LEDs, 60 LEDs/m
- Cut points every 50mm for maximum flexibility
- Voltage drop of 4V per 10m and maximum run of 10m
- For runs over 10m lengths to be connected in parallel
- Requires 12V LED driver (sold separately)
- Reel length 30m
- 3 year warranty

## Product Specs:

|                          |           |                          |           |
|--------------------------|-----------|--------------------------|-----------|
| Input Voltage            | 12~12V DC | IP Rating                | IP20      |
| Lifetime L70 (hrs)       | 35000hrs  | Lamp Base                | None      |
| Width (mm)               | 8         | Weight (Kg)              | 0.142     |
| Height (mm)              | 2         | Product Type             | LED Strip |
| Operating Temp. (Min) °C | -20°C     | Operating Temp. (Max) °C | 40°C      |

## Compliance &amp; Approvals:



## Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.