





Product Description:

LEDLine™ CX 9.6W CRI90 Tuneable White LED Strip

24V Tuneable White CRI90 LED strip is suitable for use in applications where a range of colour temperatures may be required. The tuneable white feature allows the strip to adjust colour temperature between 2500-6000K. With a beam angle of 120° individual light points are less visible creating a continuous glow. Strip can be cut to length and 2m leads soldered to special order. Reel length 30m.

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
EN-ST90BCX	9.6	2500K	350	120	White	Non Dimmable
EN-ST90BCX	9.6	4000K	700	120	White	Non Dimmable
EN-ST90BCX	9.6	6500K	380	120	White	Non Dimmable

Line Drawing Polar Curve Colour



## Feature & Benefits

- Colour exchange flexible LED strip with 3M<sup>TM</sup> self adhesive backing
- Tuneable white colour temperature between 2500-6000K
- Cut points every 100mm for maximum flexibility
- Beam angle of 120° and 17mm between LEDs, 60 LEDs per metre
- For runs over 10m individual lengths should be connected in parallel
- Reel length 30m cutting service available
- L70 30,000hrs
- 3 Year Warranty

## Product Specs:

Input Voltage	24~V DC
Lifetime L70 (hrs)	35000hrs
Weight (Kg)	0.632
Product Type	LED Strip
Operating Temp. (Max) °C	45°C

IP Rating	IP20
Width (mm)	10
Height (mm)	2
Operating Temp. (Min) °C	-20°C

## Compliance & Approvals:













## Warranty

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.