
AURORA® LIGHTING

FlexE240™




Product Description: FlexE240™ 5m Mains 240V IP65 Interconnectable LED Strip Kit

The FlexE240™ mains 240V LED strip kits are ideal for all interior and exterior accent lighting applications. Each strip is encased in a flexible IP65 silicon jacket for maximum weather protection. The interconnectable ends allow for lengths up to 30 metres to be joined together - perfect to create stunning interior, garden, landscape, and architectural lighting. Available in two kit lengths and a range of colour temperatures including RGB, for optimum scene creation.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-STKM5/30	60	3000	3500	59	120	White	Non Dimmable
EN-STKM5/40	60	4000	3500	59	120	White	Non Dimmable
EN-STKM5/BLU	60				120	White	Non Dimmable
EN-STKM5/RGB	60				120	White	Non Dimmable

Line Drawing



Polar Curve

Colour

Feature & Benefits

- IP65 rated LED strip - perfect for interior & exterior applications (not cuttable)
- IP65 rated plug and play connections allow for easy customisation
- Mains voltage power allows for long length runs to be interconnected (max single run 30 metres)
- Power lead supplied separately for installation flexibility
- Infrared remote and controller supplied as part of RGB power lead kit
- Mounting clips supplied with strip pack
- 1kV surge protection
- 3 year warranty

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	25000hrs
Width (mm)	15.3
Weight (Kg)	0.360
Product Type	LED Strip
Operating Temp. (Max) °C	40°C

Input Frequency	50/60HZ
IP Rating	IP65
Lamp Base	None
Length (mm)	5000
Height (mm)	5
Operating Temp. (Min) °C	-20°C

Compliance & Approvals:

Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.