

Product Description: T150™ 1500mm 23W Polycarbonate T8 Frosted LED Lamp

The range of LED tubes is a cost effective solution for either retrofitting existing T8 fittings or in new installations. Utilising the latest LED technology, they use 50% less energy when compared to traditional fluorescent T8 tubes.

SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	CRI
EN-T81523FR/40	4000	2050	90	23	180	80

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Impact resistant Polycarbonate
- Up to 89lm/W - high efficacy over traditional T8 fluorescent technology
- LED starter included, preventing risk of electric shock when tubes are inserted or removed from luminaire
- Suitable for use at -20° to +40°C making the range ideal for multiple applications and environments
- Life not affected by frequent switching e.g. when used with occupancy controls
- For surge protection, see table below
- All electronic ballasts and PFC capacitors must be removed from the circuit
- 3 year warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	Operating Temp. (Max) °C	40°C
Overall Diameter (mm)	29	Lamp Base	G13
Length (mm)	1498	Lamp Type	T8
Weight (Kg)	0.297	Lifetime Hours	25000hrs
Operating Temp. (Min) °C	-20		

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.