



SKU Code	Colour	Lumens	Lumens/Watt	Wattage	Beam Angle	Finish Colour
EN-T81524FR/40	4000	2400	100	24	300	Frosted White

Line Drawing

Polar Curve

Color

Product Features:

- 360° impact resistant Polycarbonate and Glass PET film T8 LED tubes
- Up to 90lm/W - high efficacy over traditional T8 fluorescent technology
- Up to 300° extra wide beam angle delivers increased light distribution
- LED starter included, preventing risk of electric shock when tubes are inserted or removed from luminaire
- Suitable for use at -20° to +40°C making the range ideal for multiple applications and environments
- Life not affected by frequent switching e.g. when used with occupancy controls
- For surge protection, see table below
- All electronic ballasts and PFC capacitors must be removed from the circuit
- 3 year warranty

Product Specs:

Input Voltage	100~265V AC	Input Frequency	50/60HZ
Power Factor	0.9	Dimmable	No
Number of LEDs	120	Technology	LED
Lifetime L70 (hrs)	25000	Operating Temp	45°C
Overall Diameter (mm)	28	Lamp Base	G13
Lamp Type	T8	Weight (Kg)	0.300
SDCM	6	LED Chip	4014

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.