

**Product Description:**

Designed to last in a tough environment, the UtiliteXL™ wall pack with cast aluminium base and polycarbonate diffuser is available in standard, microwave sensor, photocell and emergency versions with black housing.

**Product Image:**




Pack Aplique de pared UtiliteXL™ 30W IP65

**Product Features:**

- IP65 wall pack with cast aluminium base and polycarbonate diffuser.
- IK10 rating
- Non-dimmable with integrated LED driver.
- Suitable for walkways, stairways, general amenity & security areas.
- 3 year warranty

**Line Drawing Image**



**Product Specs:**

Technology	LED	Number of LEDs	60
Luminaire Distribution	Ambiente	Lifetime L70 (hrs)	25000
Input Voltage	100~240V AC	Input Frequency	50/60HZ
Dimmable	No	IP Rating	IP65
IK Rating	IK10	Fire Protection	No
Operating Env. Temp. (Max) °C	25	Optic Material	PC
Power Factor	0.9	Lamp Base	ninguno
Height (mm)	310	Width (mm)	265
Surge Protection (kV)	1.5	SDCM	4

## SKU Table and Ordering

SKU Code	Wattage	Lumens	Lumens/Watt	Colour	Beam Angle	Ra	SDCM
EN-WP102/40	30	2200	74	4000	120	80	4
EN-WP102MS/40	30	2200	74	4000	120	80	4
EN-WP102PH/40	30	2200	74	4000	120	80	4

## Compliance & Approvals:



## Warranty

This product has a warranty period of 3 aos.  
Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

**UK Enlite Sales & Distribution**  
Apex Park  
6 Little Burrow  
Welwyn Garden City AL7 4SW  
United Kingdom  
Tel : +44 (0) 1707 35 18 20