

AURORA[®]
VALUE BEYOND ILLUMINATION™



V.08

OSTIA[™]
Low Profile LED Highbay

Description

Aurora's Ostia high bay allows for significant energy saving to be achieved without sacrificing light output or performance levels. Delivering up to 107lm/W, Ostia outperforms traditional HID technology in a compact, low profile housing. 0-10V Dimming.

IES files available on the Aurora website.

Features

- Suitable for use in warehousing, manufacturing, conference centers, industrial applications, canopies and high end retail applications
- Significant energy savings and maintenance free
- High thermal efficient aluminium heatsink - low operating temperature
- 0-10V dimming function built in as standard - allows for installation with daylight or occupancy sensors
- High power factor 0.95
- Instant on/off, no re-strike delay
- Operating temperature -4°F to 140°F
- Suitable for Wet location, IP65
- IK10 glass lens 120° beam as standard, optional 90° or 60° aluminum reflectors and 60° acrylic reflector available
- Suspension, 3/4" all thread conduit entry and wall mounting options
- Supplied with 4.92ft of power cable
- (L70) at **60,000 hour lifetime**
- **5 year warranty**




NEW AR-HB2002A & AR-HBACR1

277-480V

200W UP TO 21000lm | 230W UP TO 25000lm

Compliance & Approvals



(OD) 13.28" Overall Ø
(H) 6.76" Height

Cat. No.	Voltage	Watts	HID Equiv	Lumens	lm/W	Color Temp	Life (hrs)	Dia [Ø] x H	Weight
LIGHT ENGINES - INDUSTRIAL APPLICATIONS 277-480V									
AR-HB2002A/40	277-480V	200W	>400W	20000lm	100	4000K	60,000	13.28" x 6.76"	14.85lbs
AR-HB2002A/50	277-480V	200W	>400W	20400lm	102	5000K	60,000	13.28" x 6.76"	14.85lbs
AR-HB2002A/60	277-480V	200W	>400W	21000lm	105	6000K	60,000	13.28" x 6.76"	14.85lbs
AR-HB2302A/50	277-480V	230W	>400W	24610lm	107	5000K	60,000	13.28" x 6.76"	14.85lbs

REFLECTORS - SUITABLE FOR USE WITH 200W & 230W VERSIONS

AU-RF60A	60° Highbay Reflector
AU-RF90A	90° Highbay Reflector
AU-HBACR1	60° Acrylic Highbay Reflector
AR-HBPL90	Ostia 90° Clip On Diffuser

MOUNTING BRACKET - SUITABLE FOR USE WITH 200W & 230W VERSIONS

AR-HBAKM10	3/4" NPT to M10 adaptor kit to work with AR-HB2002A and AR-HB2302A
AU-MB100A	Highbay Mounting Bracket

RETROFIT SENSOR

AR-MSR1	Microwave Sensor Remote Controller for AR-MS1-S and AR-MS1-C
AR-MS1-S	120-277V 0-10V Microwave Motion Sensor with Spring Clip



USA Sales

Aurora Lighting Inc 12035 34th St N, Suite 2, St Petersburg, FL 33716
 Tel: 727 524 4270, Fax: 727 290 3914



Warranty:

For full warranty information please visit
us.auroralighting.com/warranty

V.08: 09.01.17

auroralighting.com